

Preliminary S-BAND 18kW Transmitter

RRK273118K-690



Product Features

- Frequency from 2.7GHz to 3.1GHz
- Using High-Efficiency GaN Transistor
- Ethernet TCP/IP
- WR-284 Waveguide Output
- Forced Air Cooling

Applications

- Airport Surveillance Radar
- Weather Radar
- Industrial and Scientific
- Instrumentation Amplifier
- Defense Radar



L Description

The RRK273118K-690 Transmitter, in which state of the art SiC GaN technology is used, is designed for the high-power radar application at the frequency of 2700 ~ 3100 MHz. The transmitter is majorly used in the areas of the airport, weather, maritime, defense, industrial, and scientific applications. This GaN-based Solid State Transmitter replaces industrial magnetrons or other vacuum tubes which have been currently used in high power applications. The forced air-cooling in each module is used for user convenience, easy and quick maintenance. The redundant architecture was applied PSUs, preventing single-point failures. HPAs in the transmitter sub-system are parallelized for secure operation in the event of an HPA fault condition, also.

Electrical Specifications @ $V_{ac} = +400V$, $T_o = 25^{\circ}C$, 50Ω Input System

PARAMETER	UNIT	MIN.	TYP.	MAX.	SYMBOL
Operating Frequency	GHz	2.7	-	3.1	f_o
Operating Bandwidth	MHz	-	400	-	BW
Output Pulse Peak Power	kW	16	18	-	P_o
Input Pulse Power	dBm	-2	0	2	P_i
Gain Variation	dB	-	-	2	ΔG_P
Duty Cycle	%	-	-	10	DC
Pulse Width	us	1	-	120	PW
Amplitude Pulse Droop	dB	-	-	1.0	Droop
Harmonics 1 to N	dBc	-60	-	-	HN
Rise / Fall Time	ns	-	-	100	T_r / T_f
VSWR	-	-	-	2.0 : 1	VSWR
Power Consumption @ 10%	kW	-	6	-	P_c
Operating Voltages	VAC	+ 208 VAC 3P3W or + 380 VAC 3P4W			
Control Interface	-	Ethernet TCP/IP			
Protection & Warning Alarm (BIT)	-	DC Fail Alarm		In case of exceeding $50 \pm 3V$	
	-	Over Pulse Duty Cycle Protection		In case of over 10%	
	-	Low Input Power Alarm		Drive Amp Fault Alarm by detecting driver amp input and output power level	
	-	Low Output Power Alarm			
	-	Over Temperature Shutdown for fault units		Temperature monitoring.	

Environmental Specifications

PARAMETER	UNIT	VALUE
Operating Temperature	°C	-10 ~ +40
Storage Temperature	°C	-30 ~ +60
Humidity	RH %	0 ~ 95

Power Supply Specifications

DESCRIPTION	PERFORMANCE VALUE
Input AC Voltage	+ 208 VAC 3P3W or + 380 VAC 3P4W
Input AC Frequency	47 - 63 Hz

Mechanical Specifications

PARAMETER	UNIT	VALUE
Dimensions	mm	800 × 1540 × 1006 (Width × Height × Depth)
Weight	kg	580
RF Input Connector	-	N-Type (Female)
RF Output Connector	-	WR-284(Flange, CPR284F)
Output Monitor Connector	-	N-Type (Female)
Cooling	-	Forced Air Cooling by Fans

Mechanical Drawing

unit: mm
[inch]



800 × 1540 × 1006 (Width × Height (The height does not include the wheels) × Depth)

Note

Dimensions and Connectors may be subject to change without notice.
D-sub connectors, rf cables, and power cables are not included in this picture.

Revision History

Part Number	Release Date	Version	Description	Data Sheet Status
RRK273118K-690	January, 2025	0.1	Initial Release of Datasheet	Preliminary
RRK273118K-690	February, 2026	0.2	Revision	Preliminary



Certification

This product is manufactured by a company that is certified for the AS9100D quality management system.

RFHIC Corporation reserves the right to make changes to any products herein or to discontinue any product at any time without notice. While product specifications have been thoroughly examined for reliability, RFHIC Corporation strongly recommends buyers to verify that the information they are using is accurate before ordering. RFHIC Corporation does not assume any liability for the suitability of its products for any particular purpose, and disclaims any and all liability, including without limitation consequential or incidental damages. RFHIC products are not intended for use in life support equipment or application where malfunction of the product can be expected to result in personal injury or death. Buyer uses or sells such products for any such unintended or unauthorized application, buyer shall indemnify, protect, and hold RFHIC Corporation and its directors, officers, stockholders, employees, representatives and distributors harmless against any and all claims arising out of such unauthorized use. All sales inquiries and support should be directed to the local authorized geographic distributor for RFHIC Corporation. For customers in the US, please contact the US sales team through our website at <https://rfhicusa.com/>. For all other inquiries, please contact our international sales team through our website portal at <https://rfhic.com/contact/>