

Product Features

- Under 1GHz
- 1000W CW Psat @ 50V
- 71% Drain Efficiency @ 50V
- GaN on SiC
- Excellent Ruggedness
- Excellent Thermal Stability
- Internally Matched

Applications

- Linear Accelerator Applications
- Particle Accelerators
- Free Electron Laser



Package Type : RF24001DKR3

Description

The 550W CW RF Power Transistor is designed for particle accelerator and microwave energy applications at under 1GHz. This device is suitable for use in CW, pulse and linear applications. This high efficiency rugged device is targeted to replace industrial magnetrons and other vacuum tubes currently powering particle accelerator, and medical systems.

Typical CW Peak Power Performance*1 (V_{DS}=+50V, T_c=25°C, 50Ω)

Frequency [MHz]	Signal Type	Power Gain [dB]	Drain Efficiency [%]	Pout [W]
704		14.3	71	1014

Note

*1 Measured in the IE15550DC test board amplifier circuit.

Absolute Maximum Ratings

Rating	Symbol	Value	Unit	Condition
Drain to Source Voltage	V _{DSS}	150	V	T _c =25°C
Gate to Source Voltage	V _{GS}	-10, +2	V	T _c =25°C
Operating Voltage	V _{DD}	52	V _{DC}	
Maximum Forward Gate Current	I _{GMAX}	84	mA	T _c =25°C
Maximum Drain Current*1	I _{DMAX}	20	A	T _c =25°C
Power Dissipation	P _{DISS}	240	W	T _c =85°C
Storage Temperature	T _{STG}	-65, +150	°C	
Case Operating Temperature	T _C	-40, +150	°C	
Operating Junction Temperature*2	T _J	225	°C	
Soldering Temperature*3	T _S	245	°C	

Note

*1 Current Limit for long term, reliable operation.

*2 Continuous use at maximum temperature will affect MTTF.

*3 Refer to the Application Note(AN-002) on soldering - "Solder Condition for RFHIC's GaN Device"

Thermal Characteristics


Rating	Symbol	Value	Unit	Condition
Thermal Resistance, Junction to Case	R _{θJC}	0.69 *1	°C/W	T _c =85°C

Note

*1 Measured for the IE15550DC at dissipation power is 200W

Electrical Characteristics (Tc=25°C unless otherwise noted)

Characteristics	Conditions	Symbol	Min	Typ	Max	Unit
DC Characteristics ^{*1}						
Gate Threshold Voltage	V _{DS} = 10V	V _{GS(TH)}	-3.8	-3.0	-2.3	V _{DC}
	I _D = 200mA					
Gate Quiescent Voltage ^{*2}	V _{DS} = 50V	V _{GS(Q)}	-	-3.0	-	V _{DC}
	I _D = 200mA					
Saturated Drain Current ^{*3}	V _{DS} = 6V	I _{DS}	69.6	83.6	-	A
	V _{GS} = 2V					
Drain-Source Breakdown Voltage	V _{GS} = -8V	V _{BR}	150	-	-	V
	I _D = 41.8mA					
Gate Leakage Current	V _{GS} = -8V	I _{GLKG}	-18.4	-	-	mA
	V _{DS} = 120V					
Drain Leakage Current	V _{GS} = -8V	I _{DLKG}	-	-	33.4	mA
	V _{DS} = 120V					
RF Characteristics (Under 1GHz)						
CW Saturated Output Power ^{*4}	V _{DS} = 50V	P _{SAT}	-	1000	-	W
	I _{DQ} = 100mA					
CW Drain Efficiency ^{*4}	V _{DS} = 50V	η	-	70	-	%
	I _{DQ} = 100mA					
	P _{OUT} = P _{SAT} CW					
Output Mismatch Stress ^{*5, 6}	V _{DS} = 50V	VSWR	-	-	5:1	ψ
	I _{DQ} = 100mA					
	P _{OUT} = P _{SAT} Pulsed					



Pin Description	
Pin No	Function
1	Path A Gate
2	Path B Gate
3	Path A Drain
4	Path B Drain
5	Source

- (a) - Lid
 (b) - Lead Frame
 (c) - Flange

Dim.	INCH			MILLIMETER		
	MIN	TYP	MAX	MIN	TYP	MAX
A1	0.767	0.772	0.777	19.48	19.61	19.74
A2	0.357	0.362	0.367	9.07	9.20	9.33
B0	0.495	0.500	0.505	12.57	12.70	12.83
B1	0.145	0.150	0.155	3.68	3.81	3.94
B2	0.579	0.584	0.589	14.72	14.84	14.97
B3	0.003	0.005	0.007	0.08	0.13	0.18
B4	0.057	0.062	0.067	1.45	1.57	1.70
F1	0.806	0.811	0.816	20.47	20.60	20.73
F2	0.381	0.386	0.391	9.67	9.80	9.93
F3	0.031	0.036	0.041	0.79	0.92	1.05
F4	-	0.002	-	-	0.04	-
H1	0.127	0.148	0.170	3.22	3.77	4.32
R1 (Radius)	0.022	0.026	0.030	0.55	0.65	0.75

Revision History

Preliminary
GaN Power Transistors

Part Number	Release Date	Version	Description	Data Sheet Status
IE101J0D	May, 2026	0.1	Initial Release of Datasheet	Preliminary



Certification

This product is manufactured by a company that is certified for the AS9100D quality management system.

RFHIC Corporation reserves the right to make changes to any products herein or to discontinue any product at any time without notice. While product specifications have been thoroughly examined for reliability, RFHIC Corporation strongly recommends buyers to verify that the information they are using is accurate before ordering. RFHIC Corporation does not assume any liability for the suitability of its products for any particular purpose, and disclaims any and all liability, including without limitation consequential or incidental damages. RFHIC products are not intended for use in life support equipment or application where malfunction of the product can be expected to result in personal injury or death. Buyer uses or sells such products for any such unintended or unauthorized application, buyer shall indemnify, protect, and hold RFHIC Corporation and its directors, officers, stockholders, employees, representatives and distributors harmless against any and all claims arising out of such unauthorized use. All sales inquiries and support should be directed to the local authorized geographic distributor for RFHIC Corporation. For customers in the US, please contact the US sales team through our website at <https://rfhic.com/rfhic-us/> . For all other inquiries, please contact our international sales team through our website portal at <https://rfhic.com/contact/>